

# 2500 Litre Single Skin Oil Tank

2500 litre single skin heating oil tank with oil level monitor. Titan Environmental do recommend a bunded (tank within a tank) is used where possible to prevent groundwater pollution.



## Specifications

Oil Level Monitor	WatchmanSonic fitted as standard
Capacity Ltr/Gal	2500/550
Length (mm)	2265
Width (mm)	1285
Height (mm)	1315
Guarantee Period	2 years (one year on components)
OFCERT No	0642099401
Lid	2" Vent Cap
Tank Pack	watchmanSonic, PTFE Tape, Heldite, Heldite Applicator, Gate Valve & Filter
Fuel Type	Kerosene (C1/C2), Fuel Oil (A2) and Gas Oil/Diesel (D) as defined in BS2869 and BS EN590 including up to 7% biofuel to BS EN14214
Outlet Size	1"
Overfill Prevention	SpillStop device as standard
Optional Accessory	Tigerloop Oil De-Aerator OFCERT No 2181080901

## Details

The single skin storage tanks are specifically designed to suit domestic applications where bunding is not a legal requirement. Designed only to store kerosene central heating oil, they can be supplied in a number of options from the basic Standard Tank through to the recommended all-inclusive Talking Titan and Smart Tank versions. All tanks are also OFCERT certified, manufactured to ISO standards and are guaranteed for 2 years (components guaranteed for one year).

The Talking Titan (UK) and Smart Tanks (Ireland) are factory fitted with an oil level monitor device, WatchmanSonic. This device remotely monitors the level of oil in the tank from the comfort of your home. This electronic device eliminates the need for an external sight gauge. It is also available to fit to any existing single skin or bunded oil tank. Furthermore they are fitted with an overfill prevention device, SpillStop, and a top outlet (on request) providing extra protection against groundwater pollution.